

# SPADING MACHINES

## V SERIES

25 HP • 31", 47", 51"



## VM SERIES

30-50 HP • 49"-67"



V SERIES SPADING MACHINES are capable of penetrating the soil much deeper than conventional rotary tillage. These machines will break up ground under the top soil, cultivate 10" to 12" deep and prepare a seed bed in a single pass. Advantages include: aeration and enrichment of the soil, prevention of hard pan, relief of compaction, eliminate leeching and erosion, and are capable of incorporating organic material. Available in working widths from 39" to 67", equipped with multiple speed gearboxes and slip clutch protection for demanding conditions.

### SPECIFICATIONS

MODELS	V1003/4/100	V1003/6/120	V1003/6/130	VM6/125	VM6/135	VM6/145	VM8/170
WORKING WIDTH	39"	47"	51"	49"	53"	57"	67"
OVERALL WIDTH	41"	49"	53"	51"	55"	59"	69"
HITCH	Cat. 1	Cat. 1	Cat. 1	Cat. 1 & 2	Cat. 1 & 2	Cat. 1 & 2	Cat. 1 & 2
GEARBOX SPEEDS	4	4	4	3	3	3	3
HP REQUIRED	25	25	25	30	35	35	50
NO. OF SPADES	4	6	6	6	6	6	8
TILLING DEPTH	10"	10"	10"	12"	12"	12"	12"
PTO	Clutch	Clutch	Clutch	Clutch	Clutch	Clutch	Clutch
WEIGHT	617	758	776	981	1000	1102	1252

*Specifications subject to change without notice*

Rugged, Labor and Time Saving Products