

**Worksaver.**

***Designed.  
Engineered.  
Remarkable  
Value.***



**Worksaver®**

## **S-1030 & S-1024 Scoops**

**Digs, lifts, carries, dumps and spreads in both directions for greater productivity**



# Worksaver Models S-1030 & S-1024

- Model S-1030 easily mounts on standard Cat. I 3-pt hitch tractors
- Model S-1024 designed for 18hp to 28hp compact tractors with Cat. I and Cat. 0 (7/8" dia pins) 3-pt hitch tractors.
- Scoop is reversible for greater productivity. Forward position works as a pull scraper. Reverse position works as a shovel.
- Digs, lifts, carries, dump and spreads in either position.
- Standard trip rope activates dumping latch from the convenience of the tractor seat.
- Weld-on high carbon steel cutting edge for long life.
- Tractor top link allows easy control of digging angle.
- Extremely economical and efficient. Mounts quickly and needs no special attachments.
- Ten (10) cu./ft. capacity (S-1030)
- Eight (8) cu./ft. capacity (S-1024)

## MODEL S-1030 SPECIFICATIONS

Capacity heaped .....	Ten (10) cu./ft.
Reversible .....	Yes
Bowl width (in/mm) .....	30 / (762 mm)
Overall bowl length (in/mm) .....	31 / (787 mm)
Overall bowl height (in/mm) .....	11 / (279 mm)
Bowl construction .....	Welded steel
Bowl thickness .....	9-gauge steel
Bowl edge .....	Weld-on high carbon steel
Hitch requirement .....	Cat. I
Trip rope .....	Standard
Spring release lock .....	Standard
Shipping weight (lb/kg) .....	178 / (81 kg)
Product Computer Number .....	312000

## MODEL S-1024 SPECIFICATIONS

Capacity heaped .....	Eight (8) cu./ft.
Reversible .....	Yes
Bowl width (in/mm) .....	22.5 / (572 mm)
Overall bowl length (in/mm) .....	25 / (635 mm)
Overall bowl height (in/mm) .....	10 / (254 mm)
Bowl construction .....	Welded steel
Bowl thickness .....	9-gauge steel
Bowl edge .....	Weld-on high carbon steel
Hitch requirement .....	Cat. I / Cat. 0 w/ 7/8" pins
Trip rope .....	Standard
Spring release lock .....	Standard
Shipping weight (lb/kg) .....	160 / (73 kg)
Product Computer Number .....	312015

**▲ READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.**

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



**Worksaver, Inc.**

P.O. Box 100, Litchfield, IL 62056-0100  
 Phone: 217-324-5973 • Fax: 217-324-3356  
 E-mail: [sales@worksaver.com](mailto:sales@worksaver.com)  
 Web: [www.worksaver.com](http://www.worksaver.com)

Information Provided By:

